# **KEW DIGITAL EARTH TESTERS**

## **MODEL 4105A**

**MODEL 4105A Soft Case Model MODEL 4105A-H Hard Case Model** 



**Features** 

- Dust and drip proof.(designed to IEC 529 IP54)
- In addition to the facility for precision measurement, test leads for simplified two wire measuring system also supplied as standard accessories. (unit can be hung from the neck for simplified measurement)

The Kyoritsu's range of earth resistance testers have been

enjoying worldwide popularity and longtime sales as a high quality and high performance test instrument. Our original

constant current circuit to minimize the effect of commercial

frequencies and a synchronous rectifying circuit always

ensure a stable instrument performance. Advanced functions include self-check of the resistance of auxiliary earth spikes and testing of earth voltage, etc. All of these features ensure

- Designed to meet IEC61010-1 safety standard.
- Capable of measuring earth voltage.


trouble free operation in the field.

- Automatic warning when resistance of auxiliary earth spikes is in excess of tolerance.
- Small and lightweight. Shock resistant new case material.
- 2mA measuring current permits earth resistance tests without tripping earth leakage current breakers in the circuit under test.


## **Specifications**

	Model 4105A/4105A-H
Measurement Ranges	Earth Resistance:0-20 $\Omega$ /0-200 $\Omega$ /0-2000 $\Omega$ Earth Voltage(50,60Hz):0-200V AC
Accuracy	Earth Resistance: $\pm 2\%$ rdg $\pm 0.1\Omega$ (20 $\Omega$ range) $\pm 2\%$ rdg $\pm 3$ dgt(200 $\Omega$ /2000 $\Omega$ range) Earth Voltage: $\pm 1\%$ rdg $\pm 4$ dgt
Overload Protection	Earth Resistance:280V AC for 10 seconds across 2 of the 3 terminals Earth Voltage:300V AC for 1 minute
Safety Standard	IEC61010-1 CAT. II 300V Pollution Degree 2, IEC61557
Applicable Standards	IEC60529 IP54
Withstand Voltage	3700V AC for 1 minute
Power Source	R6P(AA)(1.5V)×6
Dimensions	105(L)×158(W)×70(D)mm
Weight	550g approx.
Accessories	7095(Test Leads)×1set(red-20m, yellow-10m, green-5m) 8032(Auxiliary earth spikes)×1set 7127(Simplified measurement probe)×1set R6P(AA)×6, Neck strap, Instruction Manual
	Carrying Case
	Soft Case (4105A) Hard Case (4105A-H)

### **Precision Earth Resistance Measurement**



# **Simplified Earth Resistance Measurement**



### **Accessories**

